



DS628

DS628 the evolution of design

- Innovative tread design is ideal for latest generation of saloons, estate cars and MPVs
- Four deep grooves delivers excellent performance, high-speed stability and superior traction on both wet and dry roads
- Rounder shoulder pitch provides an exceptionally comfortable, smooth and efficient ride

Width	Profile	Size	Marking	Ply Rating	Load Index	Speed Symbol	Rim Size (inch)	Overall Diameter(mm)	Section Width (mm)	Tread Depth (mm)
175	65	14			82	T	14	585	177	8
185	65	14			86	T	14	596	189	8
185	65	15	XL		92	H	15	621	189	8
205	65	15			94	V	15	647	209	8.5
215	65	15			96	H	15	661	211	8.5
195	60	15			88	V	15	615	201	8.5
205	60	15			91	V	15	627	209	9.5
205	60	16			92	H	16	652	209	8
215	60	16	XL		99	V	16	664	221	8.5
225	60	16			98	W	16	676	228	8.5
195	55	15			85	V	15	595	201	8
205	55	16	XL		94	W	16	632	214	8.5
215	55	16			93	W	16	642	226	8.5
225	40	18	XL		92	W	18	637	230	8.5
195	50	15			82	V	15	577	201	
185	65	15			88	H				
195	65	15			91	H				
205	55	16			94	V				
205	60	16			96	V				
215	60	16			95	V				



DS648

DS648 the evolution of high performance

- New generation high performance tyre suitable for small to medium category cars
- Aggressive lateral grooves engineered for all season driving without compromising its performance and comfort
- Computer-optimised tread pattern and profile provides excellent mileage and driving satisfaction under all road conditions

Width	Profile	Size	Marking	Ply Rating	Load Index	Speed Symbol	Rim Size (inch)	Overall Diameter(mm)	Section Width (mm)	Tread Depth
-------	---------	------	---------	------------	------------	--------------	-----------------	----------------------	--------------------	-------------

									(mm)
195	70	14		91	H	14	630	201	8
195	65	15		91	H	15	635	201	8
195	65	15		91	V	15	635	201	8
195	60	15		88	H	15	615	201	8
205	55	16	XL	94	W	16	632	214	8
195	50	15		82	V	15	577	201	8
225	45	17	XL	94	W	17	634	225	8
195	65	15		95	V				
205	55	16		94	V				



DS810

Width	Profile	Size	Marking	Ply Rating	Load Index	Speed Symbol	Rim Size (inch)	Overall Diameter(mm)	Section Width (mm)	Tread Depth (mm)
205	50	17	XL		93	W	17	638	214	
215	45	17	XL		91	W	17	626	213	
215	55	17	XL		98	W	17	668	226	
225	45	17	XL		94	W	17	634	225	
225	55	17	XL		101	W	17	680	233	
225	40	18	XL		92	W	18	637	230	
205	55	17			95	W				



DS806

Width	Profile	Size	Marking	Ply Rating	Load Index	Speed Symbol	Rim Size (inch)	Overall Diameter(mm)	Section Width (mm)	Tread Depth (mm)
175	65	14			82	T	14	585	177	
185	65	14			86	T	14	596	189	8.0

185	65	15	XL	92	H	15	621	189	
195	65	15		91	V	15	635	201	
205	65	15		94	V	15	647	209	8.5
185	60	14		82	H	14	578	189	
195	60	14		86	H	14	590	201	
195	60	15		88	V	15	615	201	8.5
205	60	15		91	V	15	627	209	8.5
215	60	16	XL	99	V	16	664	221	8.5
205	60	16		92	H	16	652	209	8.0
225	60	16		98	W	16	676	228	8.5
195	55	15		85	V	15	595	201	7.8
205	55	16	XL	94	W	16	632	214	8.5
195	50	15		82	V	15	577	201	8
195	65	15		91	H	15	635	201	
215	65	15		96	H	15	661	211	8.0
205	60	16		96	V	16	652	209	8.0
215	60	16		95	V	16	664	221	8.5
205	55	16		94	V	16	632	214	8.5
215	55	16		93	W	16	642	226	8.5
195	60	14		86	V				



➤ DS612

DS612 the evolution of all-round

- Ideal all-round tyre for all vehicles
- Offers outstanding comfort, quietness and superb handling stability under both wet and dry conditions
- Three deep grooves designed to deliver maximum water channeling power, enhancing resistance to aquaplaning

Width	Profile	Size	Marking	Ply Rating	Load Index	Speed Symbol	Rim Size (inch)	Overall Diameter(mm)	Section Width (mm)	Tread Depth (mm)
185	70	13			86	H	13	590	189	8
185	60	14			82	H	14	578	189	8

➤ DS616

DS616 the evolution of aquaplaning

- Optimised tread pattern and profile specifically engineered to ensure superb traction and responsive handling under both wet and dry road conditions
- Super slant grooves for exceptional water-drainage
- Optimised sidewall profile and tyre construction for ride comfort and cornering stability



Width	Profile	Size	Marking	Ply Rating	Load Index	Speed Symbol	Rim Size (inch)	Overall Diameter(mm)	Section Width (mm)	Tread Depth (mm)
195	65	15			91	V	15	635	201	8
195	60	14			86	H	14	590	201	8



➤ DS508

DS508 the evolution of environmental-friendly

- Innovative design enhancing environmental and performance requirement
- Combined symmetrical and compact tread pattern gives maximum water drainage, enhancing resistance to aquaplaning
- Four straight circumferential and open lateral grooves increases durability under various driving conditions

Width	Profile	Size	Marking	Ply Rating	Load Index	Speed Symbol	Rim Size (inch)	Overall Diameter(mm)	Section Width (mm)	Tread Depth (mm)
165	70	13			79	T	13	562	170	7
175	70	13			82	T	13	576	177	7.5
185	70	14			88	H	14	616	189	8
195	70	14			91	H	14			
205	70	14	XL		98	T	14	644	209	8



➤ DS519

DS519 the evolution of natural choice

- Specially formulated tread compound and wider shoulder rib gives optimise handling characteristics
- Three straight circumferential and open lateral grooves for efficient water dispersion on wet roads
- Non-interacting tread pattern reduces noise at all speeds

Width	Profile	Size	Marking	Ply Rating	Load Index	Speed Symbol	Rim Size (inch)	Overall Diameter(mm)	Section Width (mm)	Tread Depth (mm)
165	70	14			81	T	14	588	170	7



➤ DS610

DS610 the evolution of grip

- Novel tread pattern increases grip ability and skid resistance
- New optimal tread compound promotes durability under all weather and road conditions
- Suitable for various medium sedan and compact cars

Width	Profile	Size	Marking	Ply Rating	Load Index	Speed Symbol	Rim Size (inch)	Overall Diameter(mm)	Section Width (mm)	Tread Depth (mm)
155	65	13			73	T	13	532	157	7



➤ DS618

DS618 the evolution of traction

- Wide circumferential groove design ensures good traction and excellent grip ability
- Computer-optimized design promotes fuel efficiency and reduces rolling resistance
- Excellent tread wear between urban and rural running

Width	Profile	Size	Marking	Ply Rating	Load Index	Speed Symbol	Rim Size (inch)	Overall Diameter(mm)	Section Width (mm)	Tread Depth (mm)
145	70	12			69	T	12	509	150	6.5



➤ DS602

Width	Profile	Size	Marking	Ply Rating	Load Index	Speed Symbol	Rim Size (inch)	Overall Diameter(mm)	Section Width (mm)	Tread Depth (mm)
175	70	14			84	T	14	602	177	8.0
165	65	13			77	T				

➤ DS802



Width	Profile	Size	Marking	Ply Rating	Load Index	Speed Symbol	Rim Size (inch)	Overall Diameter(mm)	Section Width (mm)	Tread Depth (mm)
205	70	14		98	T					

Above constructions and specifications are subject to change with or without prior notice