



### ➤ DSR266

DSR266 the evolution of everlasting durability

- Suitable for all vehicles on motorways or major roads
- Unique tread design provides excellent traction both wet and dry conditions
- Advance tread compound helps reduce rolling resistance for fuel economy with no compromise in mileage, durability, wear regularity and noise level
- Deep, wide grooves enhance drainage efficiency and prevent stone trapping throughout the life of the tyre

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 295   | 80      | 22.5 |         | 18         | 154/152    | M            | 9.00            | 1044                  | 298                | 15               |
| 315   | 80      | 22.5 |         | 18         | 154/151    | M            | 9.00            | 1076                  | 312                | 15               |
| 11    |         | 22.5 |         | 18         | 148/145    | M            | 8.25            | 1054                  | 279                | 14               |
| 9     |         | 22.5 |         | 14         | 136/134    | M            | 6.75            | 974                   | 229                | 12               |
| 10    |         | 22.5 |         | 14         | 141/139    | M            | 7.50            | 1019                  | 254                | 12               |
| 11    |         | 24.5 |         | 16         | 149/146    | M            | 8.25            | 1104                  | 279                | 14               |
| 11    |         | 24.5 |         | 16         | 149/146    | M            | 8.25            | 1125                  | 315                | 11               |
| 275   | 80      | 22.5 |         | 16         | 145/143    | M            | 8.25            | 1012                  | 276                | 14               |
| 315   | 70      | 22.5 |         | 18         |            |              |                 |                       |                    |                  |
| 275   | 70      | 22.5 |         | 16         |            |              |                 |                       |                    |                  |
| 265   | 70      | 19.5 |         | 16         |            |              |                 |                       |                    |                  |
| 245   | 70      | 19.5 |         | 16         |            |              |                 |                       |                    |                  |



### ➤ DSR116

- Steer axle design ideal for highway use
- Excellent wear regularity and long tyre life
- Excellent handling under all situations

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 11    |         | 22.5 |         | 16         |            |              |                 |                       |                    |                  |
| 295   | 60      | 22.5 |         | 16         |            |              |                 |                       |                    |                  |
| 315   | 60      | 22.5 |         | 16         |            |              |                 |                       |                    |                  |

### ➤ DSR118

- Tread pattern designed for all round fitment on both steer and drive axles
- Excellent even wear
- Long tyre life in all road conditions



| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter(mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|----------------------|--------------------|------------------|
| 385   | 55      | 22.5 |         | 18         |            |              |                 |                      |                    |                  |
| 425   | 65      | 22.5 |         | 20         |            |              |                 |                      |                    |                  |
| 445   | 65      | 22.5 |         | 20         |            |              |                 |                      |                    |                  |



### ➤ DSR669

- Steer axle tyre designed for use in medium to high severity conditions
- Exceptional resistance to impact and lacerations
- High mileage

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 11    |         | 22.5 |         | 16         | 146/143    | M            | 8.25            | 1054                  | 279                | 13               |
| 11    |         | 24.5 |         | 16         | 149/146    |              | 8.25            | 1104                  | 279                | 13               |
| 255   | 70      | 22.5 |         | 16         |            |              |                 |                       |                    |                  |



### ➤ DSR566

- Steer axle tread pattern for long distance transport
- Excellent mileage and handling
- Low noise levels

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 11    |         | 22.5 |         | 16         | 146/143    | M            | 8.25            | 1054                  | 279                | 14.5             |
| 11    |         | 24.5 |         | 16         | 149/146    | M            | 8.25            | 1104                  | 279                | 14.5             |
| 385   | 65      | 22.5 |         | 20         |            |              |                 |                       |                    |                  |

### ➤ DSR668

- Tread designed for vehicle used in quarries and construction sites
- Excellent traction in high severity conditions
- Extreme resistance to cuts and tears



| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 12    |         | 22.5 |         | 16         | 150/147    | M            | 9.00            | 1084                  | 300                | 25               |



### ➤ DSR258

- Drive axle tyre for use in medium severity conditions
- High mileage and low noise
- Excellent handling

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 11    |         | 22.5 |         | 16         | 146/143    | M            | 8.25            | 1065                  | 279                | 21               |
| 11    |         | 24.5 |         | 16         | 149/146    |              | 8.25            | 1116                  | 279                | 21               |



### ➤ DSR08

- Drive axle tyre for use in medium-high severity conditions
- Improved mileage and regular wear
- Excellent comfort and handling

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 12    |         | 22.5 |         | 16         | 150/147    | M            | 9.00            | 1084                  | 300                | 21               |



### ➤ DSR588

- Tread pattern designed for both steer and drive axles
- High degrees of traction and stability
- Excellent mileage and regular wear

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 425   | 65      | 22.5 |         | 20         | 165        | K            | 13.00           | 1124                  | 430                | 16               |
| 445   | 65      | 22.5 |         | 20         | 169        | K            | 14.00           | 1050                  | 454                | 17               |

385 65 22.5 20



### ↳ DSR158

- Designed for drive axles on mixed roads surfaces
- High resistance to tears and cuts
- Superior even wear

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 11.00 |         | 20   |         | 18         | 152/149    | K            | 8.00            | 1085                  | 293                | 18               |
| 13    |         | 22.5 |         | 18         | 154/150    | K            | 9.75            | 1124                  | 320                | 20               |
| 9.00  |         | 20   |         | 16         |            |              |                 |                       |                    |                  |
| 10.00 |         | 20   |         | 18         |            |              |                 |                       |                    |                  |
| 12.00 |         | 20   |         | 18         |            |              |                 |                       |                    |                  |



### ↳ DSR188

- Tread pattern designed for all round fitment on both steer and drive axles
- Excellent handling and grip on wet surfaces
- Long tyre life

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 7.50  |         | 16   |         | 14         | 122/118    | K            | 6.00            | 805                   | 215                | 12               |
| 8.25  |         | 16   |         | 16         | 128/124    | K            | 6.50            | 858                   | 232                | 12.5             |
| 8.25  |         | 20   |         | 16         | 139/137    | K            | 6.50            | 962                   | 231                | 14.5             |
| 12.00 |         | 24   |         | 18         | 158/155    | K            | 8.50            | 1226                  | 315                | 16.5             |
| 13    |         | 22.5 |         | 18         | 154/150    | K            | 9.75            | 1124                  | 320                | 16.5             |
| 7.00  |         | 16   |         | 14         |            |              |                 |                       |                    |                  |
| 12.00 |         | 24   |         | 20         |            |              |                 |                       |                    |                  |



### ↳ DSR768

- Designed for drive axle usage
- High resistance to cuts and tears
- Excellent long service life

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 11    |         | 22.5 |         | 16         | 146/143    | M            | 8.25            | 1065                  | 279                | 22.5             |

### ↳ DSR08

- Drive axle tyre for long distance transport on motorways
- Excellent handling and wet grip



- Optimum even wear and tyre integrity

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter(mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|----------------------|--------------------|------------------|
| 12    |         | 22.5 |         | 16         |            |              |                 |                      |                    |                  |
| 295   | 80      | 22.5 |         | 18         |            |              |                 |                      |                    |                  |
| 315   | 80      | 22.5 |         | 18         |            |              |                 |                      |                    |                  |



### ➤ DSR355

- Tread pattern designed for all round fitment on both steer and drive axles
- Suitable for city buses and goods transport
- Improved comfort and high mileage

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 11    |         | 22.5 |         | 16         | 146/143    | M            | 8.25            | 1054                  | 279                | 22.5             |
| 11    |         | 24.5 |         | 16         | 149/146    |              | 8.25            | 1104                  | 279                | 22.5             |



### ➤ HR268

- Specialised design for city buses and suitable for all fitment on all axles
- Reinforced casing to protect against impact and scuffing
- Improved mileage and optimised regular wear

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 11    |         | 22.5 |         | 16         | 146/143    | M            | 8.25            | 1054                  | 279                | 18               |



### ➤ HR169

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 9.00  |         | 20   |         | 16         | 144/142    | K            | 7.00            | 1018                  | 259                | 15               |
| 10.00 |         | 20   |         | 16         | 146/143    | K            | 7.50            | 1054                  | 278                | 16               |

|       |      |    |         |   |      |      |     |    |
|-------|------|----|---------|---|------|------|-----|----|
| 11.00 | 20   | 18 | 152/149 | K | 8.00 | 1085 | 293 | 17 |
| 11    | 22.5 | 16 | 146/143 | M | 8.25 | 1054 | 279 | 15 |



➤ **HR166**

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 9.00  | 20      | 16   | 144/142 | K          | 7.00       | 1018         | 259             | 15.5                  |                    |                  |



➤ **HR168**

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 9.00  | 20      | 16   | 144/142 | K          | 7.00       | 1018         | 259             | 15.5                  |                    |                  |
| 10.00 | 20      | 16   | 146/143 | K          | 7.50       | 1054         | 278             | 16.5                  |                    |                  |
| 11.00 | 20      | 18   | 152/149 | K          | 8.00       | 1085         | 293             | 16                    |                    |                  |
| 12.00 | 20      | 18   | 154/151 | M          | 8.50       | 1125         | 315             | 17.5                  |                    |                  |
| 12.00 | 24      | 20   |         |            |            |              |                 |                       |                    |                  |



➤ **HR366**

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 11    | 24.5    | 16   | 149/146 |            |            |              | 8.25            | 1104                  | 279                | 14               |
| 12    | 22.5    | 16   | 150/147 | M          |            |              | 9.00            | 1084                  | 300                | 19               |




➤ **HR369**

Overall

Tread

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Diameter (mm) | Section Width (mm) | Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|---------------|--------------------|------------|
| 11    |         | 22.5 |         | 14         | 144/142    | M            | 8.25            | 1054          | 279                | 11         |



➤ **HR569**

| Width | Profile | Size | Marking | Ply Rating | Load Index | Speed Symbol | Rim Size (inch) | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) |
|-------|---------|------|---------|------------|------------|--------------|-----------------|-----------------------|--------------------|------------------|
| 315   | 80      | 22.5 |         | 18         | 154/151    | M            | 9.00            | 1076                  | 312                | 16               |

Above constructions and specifications are subject to change with or without prior notice